Cold Rolled Products



LIBERTY Galați www.libertysteelgroup.com




Liberty Galaţi is the largest integrated steel plant in Romania located in the south-eastern part of the country and one of the European leading manufacturers of metallurgical products. The production facility is fully integrated starting from raw materials, sintering, blast furnace, steel shop, heavy plate

mills, hot strip mill, cold rolling complex, galvanizing & organic coating lines. The Cold Rolled material produced by Galati plant has a high quality and meets the increasing quality demands of the customer's needs.

Applications

Product widely used for:

- General industry
- Appliances
- Automotive





Production Range

Technical Delivery Conditions

- Chemical properties according to ordered standards or specifications.
- Sizes and Tolerances according to EN10131.
- Surface aspect and surface finish according EN10130.
- Trimmed edges
- Oiled

Dimensional capability

- Coil Weight: 3.0 17.5 tons
- Inner Coil Diameter: 610 mm
- Outside Coil Diameter max 1500 mm
- Bundle delivery in sheets max 5.0 tons, bundle delivery in slit coils max 7.0 tons

Packing

- C16 domestic VCI paper and Metallic edge protection + metallic straps; 2 CS + 3 RS
- **CL6** C16 With wooden cradle
- C24 seaworthy export -Hardboard + VCI paper and Metallic edge protection + metallic straps; 2 CS + 3 RS
- **CM4** C24 with wooden cradle
- C26 seaworthy export special
 - Metallic box + VCI paper
 and Metallic edge protection
 + metallic straps; 2 CS + 3 RS
- **CM6** C26 with wooden cradle

Note

CS - Circumferential strap

RS - Radial strap

Quality Certificates

Mill's quality certificates shall be according to the material standards or customer specifications.

EN 10204 Certificate type 2.2; 3.1; 3.2 according to EN 10204.

Labeling

Plastic adhesive labels indicating:

- Made in Romania;
- Liberty logo;
- number of contract;
- size;
- standard;
- steel grade;
- coil number:
- heat number

Recommendation

The coils and sheets must be stored in clean, heated premises, which must be at least sufficiently ventilated to prevent moisture accumulation by capillarity (between sheets or coil laps), which would lead to corrosion, preferably with its packing, but no more than 6 months. Moreover, the storage temperature should be as constant as possible to avoid condensation. If storage at a low temperature cannot be avoided, the products must be warmed at about 20°C for 24 hours prior to processing.

We recommend material to be ordered with surface protection, to avoid rust formation. For material without surface protection the supplier cannot guarantee for no rust formation during transport and storage on client premises.

Equipment for coils handling should have a protective coating, e.g. sheathed non-metallic slings, and grips or C-hooks with a rubber or synthetic coating, and must be used with great care to avoid any hard impact that could mark the product.

Grades and standards

Steels for cold forming

Standard	Steel Grade	Main advantages
EN 10130	DC01; DC03; DC04	Excellent formability (deep drawing)

DC 01, DC 03

Thickness [mm]

Width [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.30 -0.31													
0.32 -0.39													
0.40 - 0.49													
0.50 - 0.59													
0.60 - 0.69													
0.70 - 0.79													
0.80 - 3.50													
3.51 - 4.00													

Standard feasibility range

Prior acceptance by the mill is mandatory

DC 04

Thickness [mm]

Width [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.33 -0.39													
0.40 - 0.49													
0.50 - 0.59													
0.60 - 0.69													
0.70 - 0.79													
0.80 - 3.50													
3.51 - 4.00													

Standard feasibility range

Prior acceptance by the mill is mandatory



Grades and standards continued...

Steel for enameling

Standard	Steel Grade	Main advantages
EN 10209 Standard Galati	DC01EK; DC04EK; DC03EK	Ready for enameling

DC01EK; DC03EK; DC04EK

Thickness [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.33 - 0.39													
0.40 - 0.49													
0.50 - 0.59													
0.60 - 0.69													
0.70 - 0.79													
0.80 - 3.50													
3.51 - 4.00													

Width [mm]

Standard feasibility range

Prior acceptance by the mill is mandatory

Structural steels

Standard	Steel Grade	Main advantages
Standard Galati	DC01_DRUMS; HC220; DC01_CS; DC01 LOW S&P	Good weldability. Excellent strength.

DC01_DRUMS; HC220; DC01_CS; DC01 LOW S&P

Thickness [mm] Width [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.50 - 0.59													
0.60 - 0.69													
0.70 - 0.79													
0.80 - 1.30													
1.31 - 3.50													

Standard feasibility range

Prior acceptance by the mill is mandatory

Grades and standards continued...

DC01_CS, DC01 LOW S&P

Thickness [mm] Width [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.30 -0.31													
0.32 -0.39													
0.40 - 0.49													
0.50 - 0.59													
0.60 - 0.69													
0.70 - 0.79													
0.80 - 3.50													
3.51 - 4.00													

Standard feasibility range

Prior acceptance by the mill is mandatory

Cold rolled steel flat products with high yield strength for cold forming

Standard	Steel Grade	Main advantages
EN 10268	HC260LA; HC300LA; HC340LA; HC380LA	Excellent strength Combination of improved weldability and good formability

HC260LA, HC300LA, HC340LA

Thickness [mm] Width [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.50 - 0.69													
0.70 - 1.19													
1.20 - 1.90													
1.91 - 3.00													

Standard feasibility range

Prior acceptance by the mill is mandatory

HC380LA

Thickness [mm] Width [mm]

	800	875	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.50 - 0.69													
0.70 - 1.19													
1.20 - 1.90													
1.91 - 2.00													
2.01 - 3.00													

Standard feasibility range

Prior acceptance by the mill is mandatory

Grades and standards continued...

Full hard

Standard	Steel Grade	Main advantages
Standard Galati	SAE1012_FH_MPS; SAE1012_FH; RH20_FH; ST-K80_FH; ST-2K50_FH; ST-OK_FH; DC01RB_ FH	Cold rolled full hard material to be used for further processing (galvanizing, annealing, other).

SAE1012_FH_MPS; SAE1012_FH; RH20_FH; ST-K80_FH; ST-2K50_FH; ST-OK_FH; DC01RB_FH

Thickness [mm]

	800	875	1000	1150	1200	1250	1280	1300	1350	1400	1450	1500	1525	1550
0.30 - 0.49														
0.50 - 0.59														
0.60 - 0.69														
0.70 - 0.79														
0.80 - 1.19														
1.20 - 1.50														
1.51 - 3.50														

Standard feasibility range

Prior acceptance by the mill is mandatory

Delivery in Sheets & Slit Coils

Delivery in sheets: max. 5.0 tons per bundle

Thickness [mm]		Width	[mm]	Sheets Length [mm]			
	875	1000	1250	1500	min	max	
0,30 - 0.39					1000	4500	
0.40 - 0.69					1000	4500	
0.7 – 1.20					1000	4500	
1.21 – 3.50					1000	4500	

Delivery in slit coils: max. 7.0 tons per bundle

Thickness [mm]	Width [mm]						
	80	100	200	735			
0.39 – 0.79							
0.80 – 3.50							

Galati Management Systems Certifications



Contact with the mill

Europe

Liberty Galati SA

Calea Smîrdan Nb 1, 800698;

Bucharest

Ethos House – 212 / 214, Gheorghe Titeica Ethos House, District 2, 020305

 $\textbf{E:} \quad \text{mariansor in. bogdan@liberty steel group. com} \\$

E: ana.vastardis@libertysteelgroup.com
E: alexandru.prunes@libertysteel.com

T: +40 374 487 723 **T:** +40 730 014 299

North Macedonia (Balkans Agency)

Liberty Skopje

16 Makedonska Brigada 18, 1000 Skopje – Macedonia

E: BalkanSales.Skopje@libertysteelgroup.com

E: contact.skopje@libertysteelgroup.com

T: +38 923 247 305 **T**: +38 923 247 312

Turkey

Korukent Sitesi

E-1 Blok K:2 D:12 Levent, Istanbul 34340, Turkey

E: sales.tr@libertysteelgroup.com

T: +90 212 275 40 95

Greece & Cyprus

Voulis 18, Syntagma, Greece

E: Petros.Korkovylos@libertysteelgroup.com

T: +30 216 070 7796 **M:** +30 695 777 5160

Customer Technical Support

E: viorel.teodoru@libertysteelgroup.com

M: +40 731 960 092

E: gabriel.jirca@libertysteelgroup.com

M: +40 751 202 068

E: cristian.dragu@libertysteelgroup.com

M: +40 733 080 156



