

## Declaration of Performance

(according to Construction Product Regulation EU No 305/2011)

No. Plate **S355J5W**

Plate **S355J5W / 1.8991** according **EN 10025-5**

To be used in Metal Structures and Composite Metal and Concrete Structures

### Liberty Steel Dalzell Limited

Park Street, Motherwell, ML1 1PU  
United Kingdom

Tel: +44 (0)1698 266100

Website: www.libertyhg.com/Dalzell


CE Marking Notified Body  
Lloyds Register Verification B.V  
K.P van der Mandelelaan 41A  
Tel: +31 (0)10 4145088 Lloyd's  
Email: Rotterdam@lr.org

System of assessment and verification of constancy of performance of the product  
System 2+

Notified factory production control certification body No. 2814 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control

Signed for and behalf of Liberty Steel Dalzell Ltd;

Name: Kenny McLeary  
Title: Technical Manager

Sign:   
Date: 04/02/22



Essential Characteristic	Performance		Harmonised Technical Specification	
Tolerances on dimensions & shape	Thickness		EN 10029	
	Flatness		EN 10029	
Yield strength (transverse)	Nominal Thickness (mm)		Values Min (Mpa)	
	>	<=		
	-	16	355	
	16	40	345	
	40	63	335	
	63	80	325	
Tensile strength (transverse)	Nominal Thickness (mm)		Values (Mpa)	
	>	<=	Min	Max
	5	100	470	630
	100	150	450	600
Elongation (transverse)	Nominal Thickness (mm)		Values Min (% , 5.65√so)	
	>	<=		
	0	40	20	
	40	63	19	
Impact strength (longitudinal)	L		27J at -50°C	
			EN10025-1 2004	
Weldability CEV	Nominal Thickness (mm)		Values Max (%)	
	>	<=		
	-	63		
	63	100	0.52	
Durability	Nominal Thickness (mm)		Values Max (%)	
	0	150	C: 0.16	
			Si: 0.50	
			Mn: 0.5 – 1.50	
			P: 0.030	
			S: 0.030	
			Nb: 0.015 – 0.060	
			V: 0.02 – 0.12	
			Ti: 0.02 – 0.10	
			Cr: 0.40 – 0.80	
			Ni: 0.65	
			Mo: 0.30	
			Cu: 0.25 - 0.55	
N: 0.009				



2814

Liberty Steel Dalzell Limited  
Park Street, Motherwell, ML1 1PU  
United Kingdom

16

Plate **S355J5W**

EN 10025-1 – 2004

Plate **S355J5W / 1.8991**

To be used in Metal Structures and Composite Metal and Concrete Structures

Tolerances on dimensions: Plate EN10029

Elongation:  
Tensile Strength:  
Yield Strength: **EN10025-5**  
Impact Strength:  
Weldability:  
Durability:  
Dangerous Substances: No Performance Determined